

Specifications

| Model | M9540 (2WD) | | M9540 (4WD) | |
|--|--|-------------------------------|--|----------------------------|
| Engine | V3800-DI-T | | | |
| Type (Make: KUBOTA) | E-CDIS, Direct Injection | | | |
| No. of cylinders/Aspiration | 4/Turbocharged | | | |
| Rated speed | rpm | 2600 | | |
| Engine net power | HP (kW) | 95 (70.8) | | |
| PTO power | HP (kW) | 84 (62.7) | | |
| Total displacement | cu.in. (cc) | 230 (3769) | | |
| Fuel tank capacity | gal. (ℓ) | 23.8 (90) | | |
| Air cleaner | Dry, dual-element | | | |
| Alternator | Amp | 45 (80A optional) | | |
| Transmission | | | | |
| No. of speeds | 12 forward/12 reverse | | | |
| Main gear shift (8 speeds) | 6/Fully synchronized | | | |
| Hydraulic-shuttle | Column-mounted lever | | | |
| Main clutch type | Hydraulic multi-plate wet disc | | | |
| Brake type | Hydraulic wet discs | | | |
| Mechanical differential lock | Rear mechanical standard | | Rear mechanical standard & front Limited Slip Automatic Differential | |
| PTO | | | | |
| PTO type | Live-independent PTO, hydraulic PTO with PTO brake, wet discs | | | |
| Speed | rpm | 540 (540/1000 optional) | | |
| Hydraulics | | | | |
| Pump capacity (3-point hitch) | gpm (ℓ/min.) | 17.0 (64.3) | | |
| 3-point hitch | Telescopic lower link ends, Telescopic stabilizers | | | |
| Category | II | | | |
| Control system | Position, draft (top link sensing) & mix control | | | |
| Lift capacity at 24 in. behind lift point | lbs. (kgf) | 4630 (2100) 7055 (3200) : OPT | | |
| No. of standard remote valves | 1 standard (2nd, 3rd & flow control valve optional) | | | |
| Other features | | | | |
| 4WD drive system | Bevel gear type | | | |
| Steering | Hydrostatic power steering | | | |
| Hood type | Full open hood, slanted, steel | | | |
| Deck type/Pedal type | Semi-flat deck with rubber mat/hanging pedals | | | |
| Panel type | Electronic | | | |
| Fender shape | Wide, Round | | | |
| Standard tire size | Front/Rear | 27×9.5-15/16.9-24 | | 9.5-20/16.9-24 |
| Dimensions & weight^(*) | | | | |
| Overall length | in. (mm) | 153 (3885) | | 148 (3760) |
| Overall height ROPS raised/ROPS retracted | in. (mm) | 90.6 (2300)/66.4 (1686) | | |
| Overall width ^(*) | in. (mm) | 77.5 (1969) | | |
| Wheelbase | in. (mm) | 88.6 (2250) | | |
| Crop clearance (Front Axle) | in. (mm) | 16.3 (415) | | |
| Tread width | Front | in. (mm) | TBA | 59.8-63.8 (1520-1620) |
| | Rear | in. (mm) | 59.1-74.8 (1500-1900) | |
| Turning radius (w/o brake) 4WD | ft. (m) | - | | 13.9 (4.25) ^(*) |
| Tractor weight | lb. (kg) | 4895 (2220) | | 5314 (2410) |
| Optional equipment | 2nd/3rd remote valve (SCD), 2nd/3rd remote valve (FD), Flow control valve, 3PT high capacity lift cylinder, Dual speed PTO kit, Rear work light kit, Drawbar clevis, Front grille guard, Suitcase weights, Wheel weights, etc. | | | |

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Some of the items pictured in this brochure are optional, and not standard equipment. Please contact your local Kubota dealer for warranty and safety information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

For complete operational information, the operator's manual should be consulted.

Not for sale in Nebraska.

(*) All dimensions measured with standard tire. (*) At 72-inch rear tire tread. (*) 4WD engaged.